



WaveMon RF-8

Personal RF Monitor



OVEREXPOSURE WARNING

Audible, visual and vibratory alarm



EMF EXPOSIMETER

Datalogger, instant & average values



ICNIRP, 2013/35/EU, FCC, SC6

Occupational/Shaped response



ELECTRIC AND MAGNETIC FIELD

Isotropic, RMS



Compliance
with ITU-T K.145



Optional
GPS
+
Altimeter
Optional

Data
geolocation



WaveMon Applications



Worker's safety



Telecommunications



Energy



Railway



Medical



Labs



Aeronautical



Industry



Defense



Optional accredited calibration

Technical Specifications

Sensor type	Isotropic, RMS diode technology	
Response	Shaped (ICNIRP 1998/2020, Directive 2013/35/EU, FCC and Safety Code 6)	
Interface	1 button ON/OFF, status and low battery LED	
Indicators	6 LEDs + Audio + Vibration	
Alarm threshold	2 limits adjustable by user	
Connectivity	Waterproof USB (for downloading data and recharging)	
Falling detection	Yes	
Autonomy	> 1 month (at 8 h/day, 5 days/week)	
Data logger	> 1 000 000 events	
Positioning	GPS and Altimeter	
Logging Interval	1 second to 60 minutes (adjustable by user)	
Averaging Interval	1 second to 60 minutes (adjustable by user)	
Battery Type	2 x AA NiMH battery rechargeable by USB	
Protection	IP 54	
LF immunity (50 – 60 Hz)	> 30 kV/m	
Temperature range	-20 / +50 °C (-4 / +122 °F) – Charging: 0 / +40 °C (+32 / +104 °F)	
Size	174 x 42.5 x 33 mm (6.8 x 1.7 x 1.3 ")	
Weight	190 g (6.7 oz.)	
	E-field	H-field
Dynamic range	1 – 300 %	2 – 300 %
Linearity	±0.5 dB (2% – 200%)	±1 dB (5% – 200%)
Isotropic deviation	±1 dB @ 1GHz	±1 dB @ 400 MHz


Product specifications and descriptions in this document subject to change without notice.

WaveMon RF-8

WaveMon Version Selection Table

Versions	Response shaped to	Frequency range and response	
		E-field	H-field
WaveMon RF-8 ICN WaveMon RF-8 EUD	ICNIRP EU Directive 2013/35	300 kHz – 8 GHz ±3.5 dB	25 MHz – 1 GHz ±1 dB (30 MHz – 700 MHz) +0 dB / -2.5 dB (700 MHz – 850 MHz) +0 dB / -5 dB (850 MHz – 1 GHz)
WaveMon RF-8 FCC	FCC	3 MHz – 8 GHz ±3.5 dB	3 MHz – 1 GHz ±1 dB (3 MHz – 400 MHz) ±2 dB (400 MHz – 850 MHz) +0 dB / -4 dB (500 MHz – 1 GHz)
WaveMon RF-8 SC6	Safety Code 6	10 MHz – 8 GHz ±3.5 dB	25 MHz – 1GHz ±2 dB (30 MHz – 800 MHz) +0 dB / -5 dB (800 MHz – 1 GHz)

WaveMon accessories



GPS
Part # W-WAVEMON-GPS

WaveMon Internal GPS



WaveStick
Part # WWMA0002

Adjustable extension stick
(73 cm / 28,74 ")



Safety cable
Part # WWMA0001

WaveMon safety attachment
cable



WaveMon Lanyard
Part # WWMA0003

Breakaway neck security lanyard